

Thermoelectric cooling unit



Description

| | |
|--|--|
| Order Number: | 0905718422 |
| Brand Name: | SoliTherm |
| Housing Material: | Stainless steel AISI 316 (V4A) |
| IP protection class to EN 60 529: | IP 66 / UL Type 12, 4, 4X |
| Note: | The torque for the mounting nuts should be 4.5 Nm. |
| Approvals: | CE |

Technical Data

| | |
|--|--|
| Cooling capacity L35L35 (EN14511-3): | 160 W |
| Cooling capacity L35L50 (EN14511-3): | 98 W |
| Air flow volume (system / unimpeded): | Umgebungskreislauf: 150 m ³ /h Schrankkreislauf: 150 m ³ /h |
| Operating Temperature Range: | -20°C - 70°C |
| UL temperature range: | -20°C - 65°C |
| Mounting: | Recessed |
| Dimensions A x B x C (D+E): | 480 x 253 x 163 mm |
| Weight: | 14.6 kg |
| Cut out dimensions: | 358 x 215 mm |
| Voltage / Frequency: | 230 V ~ 50/60 Hz |
| Current L35L35: | 0.9 A |
| Starting current: | 1.1 A |
| Max. current: | 2 A |
| Nominal power L35L35: | 190 W |
| Max. power: | 300 W |
| Fuse: | 4 A (T) |
| Connection: | Connection cable |

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SOLITHERM PELTIER - cooling units without refrigerant](#)

