

Thermoelectric cooling unit



Description

Order Number:	3200308
Brand Name:	SoliTherm Peltier
Housing Material:	Stainless steel AISI 304 (V2A)
IP protection class to EN 60 529:	IP 66 / UL Type 12, 4, 4X
Note:	The torque for the mounting nuts should be 4.5 Nm.
Approvals:	CE, cURus
Accessories:	 Condensate Kit 3152 / 3200

Technical Data

Cooling capacity L35L35 (EN14511-3):	200 W
Air flow volume (system / unimpeded):	Ambient air circuit: 120 / 260 m ³ /h Cabinet air circuit: 120 / 260 m ³ /h
Operating Temperature Range:	-20°C - 70°C
UL temperature range:	-20°C - 65°C
Mounting:	Recessed
Dimensions A x B x C (D+E):	400 x 180 x 170 (79+91) mm
Weight:	10 kg
Cut out dimensions:	370 x 155 mm
Voltage / Frequency:	48 V DC
Current L35L35:	4.7 A
Starting current:	9.5 A
Max. current:	7.5 A
Nominal power L35L35:	270 W
Max. power:	360 W
Fuse:	10 A (T)
Connection:	Connection terminal block

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SOLITHERM PELTIER - cooling units without refrigerant](#)

Order Information

Stainless steel AISI 316 (V4A) housing part no.	32003084
Box dimension	486.6 x 205 x 183.5 mm
Gross weight	12 kg
Taric code	84158300