

Thermoelectric cooling unit



Description

Order Number:	3075303
Brand Name:	SOLITHERM PELTIER
Housing Material:	Stainless steel AISI 304 (V2A)
IP protection class to EN 60 529:	IP 66 / UL Type 12, 4, 4X
Note:	The torque for the mounting nuts should be 4.5 Nm.
Approvals:	CE


Technical Data

Cooling capacity L35L35 (EN14511-3):	75 W
Air flow volume (system / unimpeded):	Ambient air circuit: 116 / 306 m ³ /h Cabinet air circuit: 58 / 182 m ³ /h
Operating Temperature Range:	-20°C - 70°C
UL temperature range:	-20°C - 65°C
Mounting:	Recessed
Dimensions A x B x C (D+E):	250 x 203 x 160 (86+74) mm
Weight:	5.2 kg
Cut out dimensions:	210 x 160 mm
Voltage / Frequency:	24 V DC
Current L35L35:	4.6 A
Starting current:	6.9 A
Max. current:	5.3 A
Power consumption:	110 W
Max. power:	127 W
Fuse:	8 A (T)
Connection:	6 pole terminal block


Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).


> [Overview Product Group SOLITHERM PELTIER - cooling without refrigerant](#)

Performance graph:


click image to enlarge

Air flow:


click image to enlarge

Cut Out Dimension:


click image to enlarge

Order Information

Stainless steel AISI 316 (V4A) housing part no.	30753034
Taric code	84158300