

Sensor operated LED lamp. Only for installation inside industrial control cabinets.



## Description

<b>Order Number:</b>	490515612
<b>Colour:</b>	RAL 9003
<b>Housing Material:</b>	Mild steel, powder coated
<b>IP protection class to EN 60 529:</b>	IP 20
<b>Included:</b>	Motion sensor NEMA 5-15 outlet (max. 10.6 A) Door contact ready Daisy Chain max. 10
<b>Note:</b>	Door Switch has to be ordered separately part no. 490505
<b>Approvals:</b>	CE
<b>UL File Number:</b>	-

**Accessories:**

 Power cable AC black, 0.7 m

 Power cable AC orange, 0.7 m

 Power cable AC black, 3 m

 Power cable AC orange, 3 m

 Daisy Chain cable AC black, 0.7 m

 Daisy Chain cable AC orange, 0.7 m

 Daisy Chain cable AC black, 1.2 m

 Daisy Chain cable AC orange, 1.2 m

 Door contact switch

## Technical Data

<b>Operating Temperature Range:</b>	-30°C - 50°C
<b>Mounting:</b>	M5 screws (x2)
<b>Dimensions A x B x C (D+E):</b>	420 x 90 x 45 mm
<b>Weight:</b>	2 kg
<b>Voltage / Frequency:</b>	115 V ~ 50/60 Hz
<b>Rated current:</b>	10.6 A
<b>Power consumption:</b>	16 W
<b>Lamp:</b>	EB-7801
<b>Luminosity:</b>	1500 lm / 5100 K
<b>Lifetime:</b>	60,000 hrs. @ 20°C
<b>Connection:</b>	Recommended external backup fuse: 17 A (T) or circuit breaker C16

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group Energy-saving LED enclosure Lamps](#)

**Performance graph:**



[click image to enlarge](#)

## Order Information

**Taric code**

94054990

---