

## COMPACT OUTDOOR



### Description

<b>Order Number:</b>	876225201
<b>Brand Name:</b>	COMPACT OUTDOOR
<b>Colour:</b>	RAL 7035
<b>Housing Material:</b>	Mild steel, powder coated
<b>Ingress Protection:</b>	IP 56 / Type 12, 3, 3R, 4
<b>Included:</b>	With enclosure heater and aluminium filter
<b>Approvals:</b>	CE, cURus, cULus

## Technical Data

<b>Cooling capacity L35L35 (EN14511-3):</b>	6.0 kW @ 50 Hz 6.2 kW @ 60 Hz
<b>Cooling capacity L35L50 (EN14511-3):</b>	4.8 kW @ 50 Hz 5.4 kW @ 60 Hz
<b>Enclosure heater:</b>	2.0 kW
<b>Compressor type:</b>	Scroll Compressor
<b>Refrigerant / GWP:</b>	R134a / 1430
<b>Refrigerant charge:</b>	1140 g / 40.2 oz
<b>High / low Pressure:</b>	32 / 6 bar 460 / 88 psi
<b>Operating Temperature Range:</b>	-40°C - 55°C
<b>Air flow volume (system / unimpeded):</b>	Ambient: 1080 / 1480 m <sup>3</sup> /h Enclosure: 935 / 1080 m <sup>3</sup> /h
<b>Mounting:</b>	Wall mounted
<b>Dimensions A x B x C (D+E):</b>	1135 x 455 x 390 mm
<b>Weight:</b>	85 kg
<b>Voltage / Frequency:</b>	380-415V 50 Hz 3~ 400-460 V 60 Hz 3~
<b>UL Voltage / Frequency:</b>	460 V - 60 Hz 3~
<b>Current L35L35:</b>	5.9 A @ 50 Hz 6.2 A @ 60 Hz
<b>Starting current:</b>	57 / 44 A
<b>Max. current:</b>	9.8 A
<b>Nominal power L35L35:</b>	3.0 kW @ 50 Hz 3.8 kW @ 60 Hz
<b>Max. power:</b>	6.3 kW
<b>Fuse:</b>	15 A (T)
<b>Max circuit ampacity:</b>	15 A
<b>Short-circuit current rating:</b>	5 kA
<b>Rated current compressor:</b>	6.4 A

**Full load current fans:**

1.3 A


**Connection:**

4 pole terminal block for power  
5 pole terminal block for signals  
3 pole connector for RS 485 interface


Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group COMPACT OUTDOOR - cooling units NEMA / Type 4X](#)

**Performance graph:**


click image to enlarge

**Cut Out Dimension:**


click image to enlarge

## Order Information

<b>Box dimensions</b>	1215 x 555 x 549.5 mm
<b>Gross weight</b>	96.5 Kg
<b>Taric code</b>	84158200