

Thermoelectric cooling unit



Description

Order Number:	6205325
Brand Name:	SOLITHERM PELTIER
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress Protection:	IP 66 / UL Type 12, 4, 4X
Included:	Condensate drain socket
Note:	The torque for the mounting nuts should be 4.5 Nm.
Approvals:	CE, cURus


Technical Data

Cooling capacity L35L35 (EN14511-3):	200 W
Operating Temperature Range:	-20°C - 70°C
UL temperature range:	-20°C - 65°C
Air flow volume (system / unimpeded):	Ambient air circuit: 106 / 260 m ³ /h Cabinet air circuit: 150 / 260 m ³ /h
Mounting:	Wall mounted (with frame)
Dimensions A x B x C (D+E):	500 x 333 x 187 mm
Weight:	21 kg
Cut out dimensions:	244 x 428 mm
Voltage / Frequency:	230 V ~ 50/60 Hz
Current L35L35:	1.1 A
Starting current:	1.7 A
Max. current:	1.2 A
Nominal power L35L35:	250 W
Max. power:	270 W
Fuse:	3 A (T)
Connection:	4 pole power connector 5 pole connector for signals


Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SOLITHERM PELTIER - cooling without refrigerant](#)

Performance graph:


click image to enlarge

Cut Out Dimension:


click image to enlarge

Order Information

Stainless steel AISI 316 (V4A) housing part no.	62053254
Box dimension	586.6 x 354 x 227 mm
Gross weight	24.3 kg
Taric code	84158300