

Thermoelectric cooling unit



Description

Order Number:	6155315
Brand Name:	SOLITHERM PELTIER
Housing Material:	Stainless steel AISI 304 (V2A)
IP protection class to EN 60 529:	IP 66 / UL Type 12, 4, 4X
Included:	Condensate drain socket
Note:	The torque for the mounting nuts should be 4.5 Nm.
Approvals:	CE, cURus

Technical Data


Cooling capacity L35L35 (EN14511-3):	150 W
Air flow volume (system / unimpeded):	Ambient air circuit: 120 / 260 m ³ /h Cabinet air circuit: 60 / 170 m ³ /h
Operating Temperature Range:	-20°C - 70°C
UL temperature range:	-20°C - 65°C
Mounting:	Wall mounted (with frame)
Dimensions A x B x C (D+E):	500 x 333 x 187 mm
Weight:	19 kg
Cut out dimensions:	244 x 428 mm
Voltage / Frequency:	120 V ~ 60 Hz
Connection:	4 pole power connector 5 pole connector for signals

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SOLITHERM PELTIER - cooling units without refrigerant](#)

Performance graph:



[click image to enlarge](#)

Cut out Dimensions:



[click image to enlarge](#)

Order Information

Stainless steel AISI 316 (V4A) housing part no.	61553154
Box dimension	586.6 x 354 x 227 mm
Gross weight	22.5 kg
Taric code	84158300