


Thermoelectric cooling unit



Description

Order Number:	6155313
Brand Name:	SOLITHERM PELTIER
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress Protection:	IP 66 / UL Type 12, 4, 4X
Note:	The torque for the mounting nuts should be 4.5 Nm.
Approvals:	CE, cURus
Accessories:	 Condensate Kit 3102 / 6155 / 6205


Technical Data

Cooling capacity L35L35 (EN14511-3):	150 W
Operating Temperature Range:	-20°C - 70°C
UL temperature range:	-20°C - 65°C
Air flow volume (system / unimpeded):	Ambient air circuit: 120 / 260 m ³ /h Cabinet air circuit: 60 / 170 m ³ /h
Mounting:	Recessed
Dimensions A x B x C (D+E):	500 x 333 x 181 (113+68) mm
Weight:	18 kg
Cut out dimensions:	302 x 472 mm
Voltage / Frequency:	120 V ~ 60 Hz
Current L35L35:	1.4 A
Starting current:	2.1 A
Max. current:	1.5 A
Nominal power L35L35:	170 W
Max. power:	180 W
Fuse:	3 A (T)
Connection:	4 pole power connector 5 pole connector for signals


Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SOLITHERM PELTIER - cooling without refrigerant](#)

Performance graph:


[click image to enlarge](#)

Cut Out Dimension:


[click image to enlarge](#)

Order Information

Stainless steel AISI 316 (V4A) housing part no.	61553134
Box dimension	586.6 x 354 x 227 mm
Gross weight	21.5 kg
Taric code	84158300