


Thermoelectric cooling unit



Description

Order Number:	6405313
Brand Name:	SOLITHERM PELTIER
Housing Material:	Stainless steel AISI 304 (V2A)
IP protection class to EN 60 529:	IP 66 / UL Type 12, 4, 4X
Approvals:	CE, cURus
Accessories:	 Condensate Kit 6405

Technical Data

Cooling capacity L35L35 (EN14511-3):	400 W
Air flow volume (system / unimpeded):	Ambient air circuit: 240 / 325 m ³ /h Cabinet air circuit: 240 / 325 m ³ /h
Operating Temperature Range:	-20°C - 70°C
UL temperature range:	-20°C - 65°C
Mounting:	Recessed
Dimensions A x B x C (D+E):	600 x 433 x 199 (133+66)
Weight:	34 kg
Cut out dimensions:	382 x 550 mm
Voltage / Frequency:	120 V ~ 60 Hz
Current L35L35:	4.1 A
Starting current:	6.5 A
Max. current:	4.5 A
Nominal power L35L35:	490 W
Max. power:	537 W
Fuse:	7 A (T)
Connection:	4 pole power connector 5 pole connector for signals

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SOLITHERM PELTIER - cooling units without refrigerant](#)

Order Information

Mit Edelstahlgehäuse AISI 316 (V4A) Bestell Nr.	64053134
Verpackungsmaße	686.6 x 454 x 232 mm
Bruttogewicht	38 kg
Zolltarifnummer	84158300