


Thermoelectric cooling unit



Description

Order Number:	6805323
Brand Name:	SOLITHERM PELTIER
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress Protection:	IP 66 / UL Type 12, 4, 4X
Note:	The torque for the mounting nuts should be 4.5 Nm.
Approvals:	CE, cURus
Accessories:	 Condensate Kit 6805


Technical Data

Cooling capacity L35L35 (EN14511-3):	800 W
Operating Temperature Range:	-20°C - 70°C
UL temperature range:	-20°C - 65°C
Air flow volume (system / unimpeded):	Ambient air circuit: 480 / 650 m ³ /h Cabinet air circuit: 480 / 650 m ³ /h
Mounting:	Recessed
Dimensions A x B x C (D+E):	975 x 517 x 202 (134+68) mm
Weight:	66 kg
Cut out dimensions:	464 x 922 mm
Voltage / Frequency:	230 V ~ 50/60 Hz
Current L35L35:	4.3 A
Starting current:	8 A
Max. current:	4.7 A
Nominal power L35L35:	979 W
Max. power:	1078 W
Fuse:	7 A (T)
Connection:	4 pole power connector 5 pole connector for signals


Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SOLITHERM PELTIER - cooling without refrigerant](#)

Performance graph:


click image to enlarge

Cut Out Dimension:


click image to enlarge

Order Information

Stainless steel AISI 316 (V4A) housing part no.	68053234
Box dimension	1060 x 612 x 260 mm
Gross weight	75.5 kg
Taric code	84158300