

CU Connect. Roof 1.5kW IP54



Description

Order Number:	951220001
Brand Name:	SLIMLINE PRO TOP
Colour:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress Protection:	IP 54
Approvals:	CE

Technical Data


Cooling capacity L35L35 (EN14511-3):	1250 W
Cooling capacity L35L50 (EN14511-3):	800 W
Compressor type:	Rotary piston
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	160 g / 5.64 oz.
High / low Pressure:	32 / 6 bar 464 / 87 psig
Operating Temperature Range:	5°C - 55°C
Air flow volume (system / unimpeded):	Ambient air circuit: 850 m ³ /h Enclosure air circuit: 645 m ³ /h
Mounting:	Roof mounted
Dimensions A x B x C (D+E):	412 x 595 x 395 mm
Weight:	41.75 kg
Voltage / Frequency:	400/460 V - 50/60 Hz 2~
Current L35L35:	1.6 A
Starting current:	8.0 A
Max. current:	2.2 A
Nominal power L35L35:	680 W
Fuse:	15 A (T)
Short-circuit current rating:	5 kA
Connection:	4 pole connector for power 5 pole connector for signals 3 pole connector for RS 485 MODBUS

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).


> [Overview Product Group SLIMLINE PRO TOP - roof mounted cooling units](#)

Performance graph:



click image to enlarge

Cut Out Dimension:



click image to enlarge

Order Information

Stainless steel housing part no.	95122002
Taric Code	84158200