

Air / Water Heat Exchanger



Description

Order Number:	2120110
Brand Name:	SLIMLINE HEX
Colour:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress Protection:	IP 55
Approvals:	CE, cURus

Technical Data


Cooling capacity L35W10 (200 l/h):	2000 W
Cooling capacity L35W10 (500 l/h):	2700 W
Coolant:	Water, light oils or similar
Operating Temperature Range:	+1°C - +72°C
Air flow volume (system / unimpeded):	518 / 920 m ³ /h
Mounting:	Wall mounted / internal
Dimensions A x B x C (D+E):	950 x 400 x 180 mm
Weight:	15 kg
Voltage / Frequency:	120 V ~ 60 Hz
Starting current:	1 A
Max. current:	1 A
Max. power:	120 W
Pressure water circuit:	10 bar
Water connection:	Rp 1/4" - inside thread with 2 connectors for pipe internal diameter of 10 mm
Fuse:	2 A (T)
Connection:	3 - pole terminal for alarms 4 - pole terminal for power

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).


> [Overview Product Group SLIMLINE HEX - air/water heat exchangers](#)

Air flow:



click image to enlarge

Cut Out Dimension:



click image to enlarge

Order Information

Stainless steel housing part no.	21201102
With solenoid valve part no.	2120100
Taric code	84158300