

Air / Water Heat Exchanger



Description

Order Number:	2130110
Brand Name:	SLIMLINE HEX
Colour:	RAL 7035
Housing Material:	Mild steel, powder coated
IP protection class to EN 60 529:	IP 55
Approvals:	CE, cURus

Technical Data

Cooling capacity L35W10 (200 l/h):	3150 W
Cooling capacity L35W10 (500 l/h):	4150 W
Coolant:	Water, light oils or similar
Air flow volume (system / unimpeded):	723 / 1340 m ³ /h
Operating Temperature Range:	+1°C - +72°C
Mounting:	Wall mounted / internal
Dimensions A x B x C (D+E):	950 x 400 x 180 mm
Weight:	17 kg
Voltage / Frequency:	120 V ~ 60 Hz
Starting current:	2.68 A
Max. current:	2.15 A
Max. power:	240 W
Pressure water circuit:	10 bar
Water connection:	Rp 1/4" - inside thread with 2 connectors for pipe internal diameter of 10 mm
Fuse:	4 A (T)
Connection:	3 - pole terminal for alarms 4 - pole terminal for power

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SLIMLINE HEX - air/water heat exchangers](#)

Order Information

Stainless steel housing part no.	21301102
With solenoid valve part no.	2130100
Taric code	84158300