





## Filter Fan



## Description

<b>Order Number:</b>	4883A3003
<b>Brand Name:</b>	SOLIFLEX
<b>Colour:</b>	RAL 9005
<b>Housing Material:</b>	ABS Plastic
<b>Ingress Protection:</b>	IP 54, Type 12
<b>Approvals:</b>	CE, cURus, cULus
<b>UL File Number:</b>	E498756

### Accessories:

	<a href="#">Hose-proof protection hood FC 4000 400</a>
	<a href="#">Hose-proof protection hood FC 4000 400 FDA</a>
	<a href="#">Adjustable Thermostat NO</a>
	<a href="#">Filter media</a>

## Technical Data

<b>Operating Temperature Range:</b>	-10°C - +55°C
<b>Air flow unimpeded:</b>	820 m <sup>3</sup> /h - 930 m <sup>3</sup> /h
<b>Dimensions A x B x C (D+E):</b>	325 x 325 x 158.5 mm
<b>Weight:</b>	4.25 kg
<b>Cut out dimensions:</b>	291 x 291 (+1.5) mm
<b>Voltage / Frequency:</b>	120 V ~ 60 Hz
<b>Rated current:</b>	1.5 A
<b>Power consumption:</b>	172 W
<b>Degree of separation:</b>	85% - DIN 24185
<b>Wall thickness:</b>	1.5 - 2.5 mm
<b>Filter class:</b>	G3 according to EN 779
<b>Installation:</b>	Elastic clips or by 4 self-threading screws
<b>Noise level:</b>	72 dB(A)


Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SOLIFLEX - Filter fans & exhaust filters](#)


**Air flow:**

Q = Air flow [cfm]  
P = Static pressure [inH2O]



[click image to enlarge](#)

**Cut Out Dimension:**



[click image to enlarge](#)

## Order Information

<b>Taric code</b>	84145915
<b>GTIN (EAN)</b>	5350604100763