

## Control Cabinet Air Conditioner



### Description

<b>Order Number:</b>	43042001
<b>Brand Name:</b>	COMPACT INDOOR
<b>Colour:</b>	RAL 7035
<b>Housing Material:</b>	Mild steel, powder coated
<b>Ingress Protection:</b>	IP 54 / TYPE 12
<b>Approvals:</b>	CE, cURus, cULus

#### Accessories:



[Stainless Steel Filter Holder 4304](#)



[Fibre Filter Media 4304](#)




[Washable Aluminium Filter 4304](#)


## Technical Data

<b>Cooling capacity L35L35 (EN14511-3):</b>	320 W @ 50 Hz 360 W @ 60 Hz
<b>Cooling capacity L35L50 (EN14511-3):</b>	200 W @ 50 Hz 220 W @ 60 Hz
<b>Compressor type:</b>	Reciprocating compressor
<b>Refrigerant / GWP:</b>	R134a / 1430
<b>Refrigerant charge:</b>	79 g / 2.78 oz
<b>High / low Pressure:</b>	25 / 6 bar 365 / 88 psig
<b>Operating Temperature Range:</b>	10°C - 55°C
<b>Air flow volume (system / unimpeded):</b>	Ambient air circuit: 90 / 250 m <sup>3</sup> /h Cabinet air circuit: 115 / 136 m <sup>3</sup> /h
<b>Mounting:</b>	External
<b>Dimensions A x B x C (D+E):</b>	501.6 x 280 x 200 mm
<b>Weight:</b>	26 kg
<b>Cut out dimensions:</b>	480 x 240 mm
<b>Voltage / Frequency:</b>	400/460 V ~ 50/60 Hz 2~
<b>UL Voltage / Frequency:</b>	400/460 V ~ 60 Hz 2~
<b>Current L35L35:</b>	1.1 A @ 50 Hz 1.0 A @ 60 Hz
<b>Starting current:</b>	3.8 A
<b>Max. current:</b>	1.4 A
<b>Nominal power L35L35:</b>	440 W
<b>Max. power:</b>	550 W
<b>Fuse:</b>	2 x 3.6 A (T)
<b>Short-circuit current rating:</b>	5 kA
<b>Connection:</b>	Connection terminal block


Please click on the graphics to download.  
 More CAD drawings can be found under [Product Download](#).  
 > [Overview Product Group COMPACT INDOOR - reliable and economical](#)

**Performance graph:**


click image to enlarge

**Air flow:**


click image to enlarge

**Cut Out Dimension:**


CUTOUT FOR EXTERNAL

click image to enlarge

## Order Information

<b>Stainless steel housing part no.</b>	4304202
<b>Box dimensions</b>	535 x 323 x 225 mm
<b>Gross weight</b>	27 kg
<b>Taric code</b>	84158200