

Control Cabinet Air Conditioner



Description

Order Number:	43042001
Brand Name:	COMPACT INDOOR
Colour:	RAL 7035
Housing Material:	Mild steel, powder coated
IP protection class to EN 60 529:	IP 54 / TYPE 12
Approvals:	CE, cURus, cULus

Accessories:



[Stainless Steel Filter Holder 4304](#)



[Fibre Filter Media 4304](#)



[Washable Aluminium Filter 4304](#)

Technical Data


Cooling capacity L35L35 (EN14511-3):	320 W @ 50 Hz 360 W @ 60 Hz
Cooling capacity L35L50 (EN14511-3):	200 W @ 50 Hz 220 W @ 60 Hz
Compressor type:	Reciprocating compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	79 g / 2.78 oz
High / low Pressure:	25 / 6 bar 365 / 88 psig
Air flow volume (system / unimpeded):	Ambient air circuit: 90 / 250 m ³ /h Cabinet air circuit: 115 / 136 m ³ /h
Operating Temperature Range:	10°C - 55°C
Mounting:	External
Dimensions A x B x C (D+E):	501.6 x 280 x 200 mm
Weight:	26 kg
Cut out dimensions:	480 x 240 mm
Voltage / Frequency:	400/460 V ~ 50/60 Hz 2~
UL Voltage / Frequency:	400/460 V ~ 60 Hz 2~
Current L35L35:	1.1 A @ 50 Hz 1.0 A @ 60 Hz
Starting current:	3.8 A
Max. current:	1.4 A
Nominal power L35L35:	440 W
Max. power:	550 W
Fuse:	2 x 3.6 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).


> [Overview Product Group COMPACT INDOOR - reliable and economical](#)

Performance graph:




click image to enlarge

Air flow:



click image to enlarge

Cut out Dimensions:



click image to enlarge

Order Information

Stainless steel housing part no.	4304202
Box dimensions	535 x 323 x 225 mm
Gross weight	27 kg
Taric code	84158200