





Filter Fan



Description

Order Number:	4883A9000
Brand Name:	SOLIFLEX
Colour:	RAL 7035
Housing Material:	ABS Plastic
Ingress Protection:	IP 54, Type 12
Approvals:	CE, cURus, cULus
UL File Number:	E498756

Accessories:

	Hose-proof protection hood FC 4000 400
	Hose-proof protection hood FC 4000 400 FDA
	Adjustable Thermostat NO
	Filter media

Technical Data

Operating Temperature Range:	-10°C - +55°C
Air flow unimpeded:	820 m ³ /h
Dimensions A x B x C (D+E):	325 x 325 x 158.5 mm
Weight:	4.25 kg
Cut out dimensions:	291 x 291 (+1.5) mm
Voltage / Frequency:	400/460 V ~ 50/60 Hz
Rated current:	0.20 A / 0.24 A
Power consumption:	110 W / 145 W
Wall thickness:	1.5 - 2.5 mm
Filter class:	G3 according to EN 779
Installation:	Elastic clips, optional screw mounting
Noise level:	66 dB(A) @ 50 Hz 69.2 dB(A) @ 60 Hz


Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SOLIFLEX - Filter fans & exhaust filters](#)


Air flow:

Q = Air flow [cfm]
P = Static pressure [inH2O]



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)

Order Information

Taric code	84145915
GTIN (EAN)	5350604100831