



Description

Order Number:	6512203001
Brand Name:	SOLITHERM CHILL
Colour:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress Protection:	IP 54
Approvals:	CE, UL 508A

Technical Data

Cooling capacity W18L35 (50/60 Hz):	12,000 / 13,300 W
Control accuracy:	2 K
Refrigerant / GWP:	R513A / GWP 631
Tank capacity:	59 l
Housing dimensions:	595 x 595 / 615 x 1,436 / 1,505 (incl. fan)
Operational temperature range - coolant:	13°C - 25°C
Operational temperature range - ambient:	10°C - 50°C
Nominal outlet pressure (50/60 Hz):	2.5 / 5.0 bar @ 30 l/min.
Mounting:	Free-standing
Weight:	160 kg
Voltage / Frequency:	400/460 V - 50/60 Hz 3~
Voltage tolerance:	±10%
Power consumption (50/60 Hz):	5300 / 7000 W
Max. power consumption (50/60 Hz):	7200 / 9500 W
Max. current (50/60 Hz):	13.0 / 14.0 A
Circuit breaker:	Type C 3 x 20 A

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SOLITHERM CHILL - Industrial liquid cooling](#)

