



Description

| | |
|--|---------------------------|
| Order Number: | 6512201001 |
| Brand Name: | SOLITHERM CHILL |
| Colour: | RAL 7035 |
| Housing Material: | Mild steel, powder coated |
| IP protection class to EN 60 529: | IP 54 |
| Approvals: | CE, UL 508A |

Technical Data

| | |
|---|---|
| Cooling capacity W18L35 (50/60 Hz): | 12,000 / 13,300 W |
| Control accuracy: | 0.5 K |
| Refrigerant / GWP: | R513A / GWP 631 |
| Tank capacity: | 59 l |
| Housing dimensions: | 595 x 595 / 615 x 1,436 / 1,505 (incl. fan) |
| Operational temperature range - coolant: | 13°C - 25°C |
| Operational temperature range - ambient: | 10°C - 50°C |
| Nominal outlet pressure (50/60 Hz): | 2.5 / 5.0 bar @ 30 l/min. |
| Mounting: | Free-standing |
| Power consumption (50/60 Hz): | 5300 / 7000 W |
| Max. power consumption (50/60 Hz): | 7200 / 9500 W |
| Circuit breaker: | Type C 3 x 20 A |

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SOLITHERM CHILL - Industrial liquid cooling](#)

