

Outdoor filter fan SF 4732 - 120V



Description

Order Number:	4732152503
Brand Name:	SOLIVENT PRO
Colour:	RAL 9005
Housing Material:	PC plastic
IP protection class to EN 60 529:	IP 54
UL Typ (UL 50E):	12, 3R
Approvals:	CE, cURus, cULus
UL File Number:	E498756

Technical Data

Air flow unimpeded IP 54:	696 / 717 m ³ /hr
Air flow with exhaust filter IP 54:	450 / 450 m ³ /hr
Operating Temperature Range:	-40°C - 70°C
Storage temperature range:	-40°C - 70°C
Mounting:	Wall mounted
Dimensions A x B x C (D+E):	325.5 x 325.5 x 165.2 (11.6+153.6) mm
Weight:	4.8 kg
Cut out dimensions:	292 x 292 mm
Voltage / Frequency:	120 V ~ 50/60 Hz
Rated current:	0.65 / 0.88 A
Power consumption:	72 / 100 W
Wall thickness:	1-3 mm
Noise level:	61 dB(A)
Fuse:	1 A (T)
Connection:	Spring terminal

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).


> [Overview Product Group SOLIVENT PRO - Filter fans & exhaust filters](#)

Air flow:



click image to enlarge

Cooling capacity:



click image to enlarge

Cut out Dimensions:



click image to enlarge

Order Information

Order number	IP rating	UL Type	RAL colour	Flow type ¹⁾	Air flow (m ³ /h) ²⁾	Air flow with exhaust filter (m ³ /h)
4732152501	54	12 / 3R	RAL 7035	B	696 / 717 m ³ /hr	450 / 450 m ³ /hr
4732152503	54	12 / 3R	RAL 9005	B	696 / 717 m ³ /hr	450 / 450 m ³ /hr
473215R2501	54	12 / 3R	RAL 7035	S	549 / 542 m ³ /hr	N/A
473215R2503	54	12 / 3R	RAL 9005	S	549 / 542 m ³ /hr	N/A

¹⁾ B = Blowing - from ambient into the enclosure (standard version)
S = Suction - from enclosure to ambient (on request)

²⁾ unimpeded 50/60 Hz