

Thermoelectric cooling unit



Description

Order Number: 3035303

Brand Name: SOLITHERM PELTIER

Housing Material: Stainless steel AISI 304 (V2A)

Ingress Protection: IP 66 / UL Type 12, 4, 4X

Note: The torque for the mounting nuts should be 4.5 Nm.

Approvals: CE

Accessories:



[Condensate Kit 3030 / 3050](#)


Technical Data

Cooling capacity L35L35 (EN14511-3):	30 W
Operating Temperature Range:	-20°C - 70°C
UL temperature range:	-20°C - 65°C
Air flow volume (system / unimpeded):	Ambient air circuit: 39 / 75 m ³ /h Cabinet air circuit: 20 / 62 m ³ /h
Mounting:	Recessed
Dimensions A x B x C (D+E):	110 x 154 x 129 (62+67) mm
Weight:	1.8 kg
Cut out dimensions:	122 x 82 mm
Voltage / Frequency:	24 V DC
Current L35L35:	2 A
Starting current:	4 A
Max. current:	2.2 A
Nominal power L35L35:	44 W
Max. power:	52 W
Fuse:	5 A (T)
Connection:	Connection terminal block


Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).


> [Overview Product Group SOLITHERM PELTIER - cooling without refrigerant](#)

Performance graph:


click image to enlarge

Air flow:


click image to enlarge

Cut Out Dimension:


click image to enlarge

Order Information

Stainless steel AISI 316 (V4A) housing part no.	30353034
Box dimension	244 x 187 x 174 mm
Gross weight	2.5 kg
Taric code	84158300