

Roof Filter Fan




Description

| | |
|----------------------------|---------------------------|
| Order Number: | 6095A3000 |
| Brand Name: | SOLIFLEX |
| Color: | RAL 7035 |
| Housing Material: | Mild steel, powder coated |
| Ingress protection: | IP 54, Type 1, 12 |
| Approvals: | CE, cURus |

Technical data

| | |
|-------------------------------------|------------------------------|
| Operating temperature range: | 14°F - +131°F |
| Air volume flow unimpeded: | 570 cfm |
| Static pressure: | 750 Pa |
| Mounting: | top mounted |
| Dimension H x W x D: | 5.8 x 18 x 18 inch |
| Weight: | 7 kg |
| Cut out dimensions: | 11.46 x 11.46 inch |
| Voltage / Frequency: | 115 V ~ 60 Hz |
| Rated current: | 1.9 A |
| Power consumption: | 225 W |
| Degree of separation: | 85% - DIN 24185 |
| Filter class: | G3 (Aluminium optional) |
| Noise level: | 76 dB(A) |
| Connection: | 4 - poliger Push-fit Stecker |

Cut out dimensions:



Order Information

| | |
|-------------------|---------------|
| Taric code | 84145915 |
| GTIN (EAN) | 5350604100893 |