

## SOLITHERM PROTEC



### Description

<b>Order Number:</b>	87402584
<b>Brand Name:</b>	SOLITHERM PROTEC
<b>Housing Material:</b>	Stainless steel AISI 316 (V4A)
<b>Ingress protection to EN 60 529:</b>	IP 56 / Type 12, 3, 3R, 4, 4X
<b>Optional:</b>	With stainless steel housing # 87402082USL
<b>Approvals:</b>	CE, cULus
<b>UL File Number:</b>	E498756

## Technical data

<b>Cooling capacity 95F/95F:</b>	3900 W @ 50 Hz 4300 W @ 60 Hz
<b>Cooling capacity 95F/122F:</b>	3300 W @ 50 Hz 3400 W @ 60 Hz
<b>EER 95F95F:</b>	2.0 / 1.7
<b>Enclosure heater:</b>	2,000 W
<b>Compressor type:</b>	Reciprocating compressor
<b>Refrigerant / GWP:</b>	R 513A / 630
<b>Refrigerant charge:</b>	701 g / 24.7 oz
<b>High / low pressure:</b>	35 / 6 bar 508 / 88 psig
<b>Air volume flow (system / unimpeded):</b>	Ambient: 640 / 880 cfm Enclosure: 520 / 880 cfm
<b>Operating temperature range:</b>	-40°C - +60°C
<b>UL temperature range:</b>	-40°C - +60°C
<b>Mounting:</b>	Wall mounted
<b>Dimension H x W x D:</b>	40.9 x 17.9 x 14.6 inch
<b>Weight:</b>	65 kg
<b>Voltage / Frequency:</b>	380-415 V 50 Hz 3~ 400-460 V 60 Hz 3~
<b>UL Voltage / Frequency:</b>	460 V / 60Hz 3~
<b>Current 95F95F:</b>	3.6 A @ 50 Hz 3.8 A @ 60 H
<b>Starting current:</b>	19 A
<b>Max. current:</b>	5.0 A
<b>Nominal power 95F95F:</b>	1.9 kW @ 50 Hz 2.4 kW @ 60 Hz
<b>Max. power:</b>	3.5 kW
<b>Fuse:</b>	15 A (T)
<b>Max circuit ampacity:</b>	15 A
<b>Short-circuit current rating:</b>	5 kA

<b>Rated current compressor:</b>	3.0 A
<b>Full load current fans:</b>	1.3 A
<b>Connection:</b>	5 pole terminal block for signals 4 pole terminal block for power 3 pole terminal block for RS 485 MODBUS



## Order Information

**Zolltarifnummer**

84158200

---