

Filter Fan



Description


Order Number:	4210D2100
Brand Name:	SOLIFLEX
Color:	RAL 7035
Housing Material:	ABS Plastic
Ingress protection:	Type 12
Note:	Umgekehrter Luftstrom
Optional:	Different housing colours available on request With NEMA 3R protection part no. 4210D2130
Approvals:	CE, cURus, cULus, CSA

Technical data



Operating temperature range:	14°F - +131°F
Air volume flow unimpeded:	38 cfm
Static pressure:	0.32 inH2O
Dimension H x W x D:	5.9 x 5.9 x 2.9 inch
Weight:	1.10 lbs
Cut out dimensions:	4.9 x 4.9 (+0.06) inch
Voltage / Frequency:	24 V DC
Rated current:	0.31 A
Power consumption:	7.4 W
Degree of separation:	85% - DIN 24185
Wall thickness:	0.04 - 0.08 in.
Filter class:	G3 according to EN 779
Installation:	Elastic clips or by 4 self-threading screws
Noise level:	48 dB(A)

Air flow:

Q = Air flow [m3/h]
P = Static pressure [Pa]



Cut out dimensions:



Order Information

In RAL 9005	4210D2103
Taric code	84145915
GTIN (EAN)	5350604100275