

## Roof Filter Fan




## Description

<b>Order Number:</b>	6064A3000
<b>Brand Name:</b>	SOLIFLEX
<b>Color:</b>	RAL 7035
<b>Housing Material:</b>	Mild steel, powder coated
<b>Ingress protection to EN 60 529:</b>	IP 54, Type 1, 12
<b>Optional:</b>	Aluminium filter kit Temperature control thermostat Alarm thermostat
<b>Approvals:</b>	CE, cURus

## Technical data

<b>Air volume flow (system / unimpeded):</b>	285 m <sup>3</sup> /hr
<b>Air flow unimpeded IP 54:</b>	290 CFM
<b>Operating temperature range:</b>	-10°C - 55°C
<b>Static pressure:</b>	63 Pa
<b>Mounting:</b>	top mounted
<b>Dimension H x W x D:</b>	5.8 x 18 x 18 inch
<b>Weight:</b>	7 kg
<b>Cut out dimensions:</b>	11.46 x 11.46 inch
<b>Voltage / Frequency:</b>	120 V ~ 60 Hz
<b>Rated current:</b>	0.5 A
<b>Power consumption:</b>	57 W
<b>Degree of separation IP 54:</b>	85% - DIN 24185
<b>Filter class (ISO 16890):</b>	G3 (Aluminium optional)
<b>Noise level:</b>	51 dB(A)
<b>Connection:</b>	4 - poliger Push-fit Stecker

**Cut out Dimensions:**



## Order Information

<b>Taric code</b>	84145915
<b>GTIN (EAN)</b>	5350604100893