

## Filter Fan



## Description


<b>Order Number:</b>	4830A3100
<b>Brand Name:</b>	SOLIFLEX
<b>Color:</b>	RAL 7035
<b>Housing Material:</b>	ABS Plastic
<b>Ingress protection:</b>	IP 54, Type 12, 3R
<b>Note:</b>	Umgekehrter Luftstrom
<b>Optional:</b>	Different housing colours available on request With NEMA 3R protection part no. 4830A3130
<b>Approvals:</b>	CE, cURus, cULus

## Technical data



<b>Operating temperature range:</b>	14°F - +131°F
<b>Air volume flow unimpeded:</b>	359 cfm
<b>Static pressure:</b>	0.78 inH2O
<b>Dimension H x W x D:</b>	12.8 x 12.8 x 6.3 inch
<b>Weight:</b>	6.8 lbs
<b>Cut out dimensions:</b>	11.5 x 11.5 (+0.06) inch
<b>Voltage / Frequency:</b>	120 V ~ 60 Hz
<b>Rated current:</b>	0.73 A
<b>Power consumption:</b>	83 W
<b>Degree of separation:</b>	85% - DIN 24185
<b>Wall thickness:</b>	0.06 - 0.10 in.
<b>Filter class:</b>	G3 according to EN 779
<b>Installation:</b>	Elastic clips
<b>Noise level:</b>	69.2 dB(A)

**Air flow:**

Q = Air flow [m3/h]  
P = Static pressure [Pa]



**Cut out dimensions:**



## Order Information

<b>In RAL 9005</b>	4830A3103
<b>Taric code</b>	84145915
<b>GTIN (EAN)</b>	5350604100633