

## Filterless enclosure air conditioner




### Description

<b>Order Number:</b>	42742001
<b>Brand Name:</b>	SLIMLINE
<b>Color:</b>	RAL 7035
<b>Housing Material:</b>	Mild steel, powder coated
<b>Ingress protection:</b>	TYPE 12
<b>Approvals:</b>	CE / cURus


## Technical data

<b>Cooling capacity 95F/95F:</b>	5120 BTU
<b>Cooling capacity 95F/122F:</b>	4100 BTU
<b>Compressor type:</b>	Rotary piston compressor
<b>Refrigerant / GWP:</b>	R134a / 1430
<b>Refrigerant charge:</b>	505 g / 17.8 oz
<b>High / low pressure:</b>	37 / 11.3 bar 536 / 164 psig
<b>Operating temperature range:</b>	50°F - 131°F
<b>Air volume flow (system / unimpeded):</b>	Ambient air circuit: 253 / 706 cfm Cabinet air circuit: 118 / 500 cfm
<b>Mounting:</b>	Wall mounted / Recessed
<b>Dimension H x W x D:</b>	61.02 x 15.55 x 5.71 in.
<b>Weight:</b>	110 lbs.
<b>Cut out dimensions:</b>	60.28 x 14.80 in.
<b>Voltage / Frequency:</b>	380-415 V 50 Hz 3~ 400-460 V 60 Hz 3~
<b>Current 95F95F:</b>	1.8 A @ 50 Hz 2.0 A @ 60 Hz
<b>Starting current:</b>	13 A
<b>Max. current:</b>	3.2 A
<b>Nominal power 95F95F:</b>	1.0 kW @ 50 Hz 1.2 kW @ 60 Hz
<b>Max. power:</b>	1.53 kW
<b>Fuse:</b>	3 x 6 A (T)
<b>Short-circuit current rating:</b>	5 kA
<b>Connection:</b>	Connection terminal block


**Performance graph:**



**Air flow:**



**Cut out dimensions:**



## Order Information

<b>Box dimensions</b>	1,627 x 496 x 204 mm
<b>Gross weight</b>	56 kg
<b>Taric code</b>	84158200
<b>GTIN (EAN)</b>	5350604371361