

Enclosure air conditioner




Description

Order Number:	43050001
Brand Name:	COMPACT INDOOR
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection to EN 60 529:	TYPE 12
Approvals:	CE, cURus, cULus


Technical data

Cooling capacity 95F/95F:	2120 BTU
Cooling capacity 95F/122F:	1500 BTU
Compressor type:	Reciprocating compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	127 g / 4.5 oz
High / low pressure:	23.3 / 5.3 bar 338 / 77 psig
Air volume flow (system / unimpeded):	Ambient air circuit: 256 / 324 cfm Cabinet air circuit: 118 / 147 cfm
Operating temperature range:	68°F - 131°F
Mounting:	Wandanbau
Dimension H x W x D:	650 x 315 x 260 mm
Weight:	61 lbs.
Cut out dimensions:	25.00 x 10.83 in.
Voltage / Frequency:	230 V ~ 50/60 Hz
UL Voltage / Frequency:	230 V ~ 60 Hz
Current 95F95F:	2.1 A
Starting current:	9.8 A
Max. current:	2.5 A
Nominal power 95F95F:	370 W @ 50 Hz 400 W @ 60 Hz
Max. power:	510 W
Fuse:	6 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block


Performance graph:



Air flow:



Cut out Dimensions:



Order Information

Stainless steel housing part no.	4305002
Mit Kondensatverdunstung Bestell Nr.	43050101
Verpackungsmaße	685 x 353 x 295 mm
Bruttogewicht	29.5 kg
Taric code	84158200