

## Air to Water Heat Exchanger



### Description


<b>Order Number:</b>	2125110
<b>Brand Name:</b>	SLIMLINE HEX
<b>Color:</b>	RAL 7035
<b>Housing Material:</b>	Mild steel, powder coated
<b>Ingress protection:</b>	NEMA 12
<b>Approvals:</b>	CE

## Technical data


<b>Cooling capacity 95F/W50F (53 GPH):</b>	8530 BTU
<b>Cooling capacity 95F/W50F (132 GPH):</b>	10750 BTU (only w/o water flow regulator)
<b>Coolant:</b>	Water, light oils or similar
<b>Operating temperature range:</b>	+34°F - +162°F
<b>Air volume flow (system / unimpeded):</b>	311 / 765 cfm
<b>Mounting:</b>	Wall mounted / Internal
<b>Dimension H x W x D:</b>	36.85 x 10.31 x 5.77 in.
<b>Weight:</b>	39.68 lbs
<b>Voltage / Frequency:</b>	120 V ~ 60 Hz
<b>Starting current:</b>	3 A
<b>Max. current:</b>	1.7 A
<b>Max. power:</b>	200 W
<b>Pressure water circuit:</b>	10 bar
<b>Water connection:</b>	Rp 1/4" - inside thread with 2 connectors for pipe internal diameter of 0.39 in.
<b>Fuse:</b>	5 A (T)
<b>Connection:</b>	Connection terminals

**Performance graph:**


**$\Delta T$**  = Temperature difference between air intake and cooling  
**P** = Cooling capacity



**Air flow:**



**Cut out dimensions:**



## Order Information

<b>Stainless steel housing part no.</b>	21251102
<b>With proportional water flow regulator part no. *** (control range +20°C - +50°C)</b>	2125100
<b>Verpackungsmaße</b>	1033.6 x 279 x 183.5 mm
<b>Bruttogewicht</b>	21 kg
<b>Taric code</b>	84158300
<b>GTIN (EAN)</b>	5350604210868