

Thermoelectric cooler




Description

Order Number:	3200305
Brand Name:	SOLITHERM PELTIER
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress protection to EN 60 529:	IP 66 / UL Type 12, 4, 4X
Note:	The torque for the mounting nuts should be 4.5 Nm.
Approvals:	CE, cURus


Technical data

Cooling capacity 95F/95F:	680 BTU
Air volume flow (system / unimpeded):	Ambient air circuit: 70 / 153 cfm Cabinet air circuit: 70 / 153 cfm
Operating temperature range:	-4°F - 158°F
UL temperature range:	-4°F - 149°F
Mounting:	External (with frame)
Dimension H x W x D:	19.7 x 7.4 x 6.9 inch
Weight:	30 lbs.
Cut out dimensions:	18.5 x 6.1 inch
Voltage / Frequency:	24 V DC
Current 95F95F:	11.3 A
Starting current:	16.9 A
Max. current:	12.9 A
Nominal power 95F95F:	270 W
Max. power:	311 W
Fuse:	18 A (T)
Connection:	Connection terminal block


Performance graph:



Air flow:



Cut out Dimensions:



Order Information

Stainless steel AISI 316 (V4A) housing part no.	32003054
Verpackungsmaße	486.6 x 205 x 183.5 mm
Bruttogewicht	15.7 kg
Taric code	84158300