

Enclosure air conditioner




Description

Order Number:	43201001
Brand Name:	COMPACT INDOOR
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection:	TYPE 12
Approvals:	CE, cURus, cULus


Technical data

Cooling capacity 95F/95F:	6,830 BTU
Cooling capacity 95F/122F:	5,630 BTU
Compressor type:	Rotary piston compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	620 g / 21.9 oz
High / low pressure:	29 / 6 bar 425 / 88 psig
Operating temperature range:	50°F - 131°F
Air volume flow (system / unimpeded):	Ambient air circuit: 383 / 706 cfm Cabinet air circuit: 277 / 500 cfm
Mounting:	External
Dimension H x W x D:	38.6 x 15.5 x 10.2 inch
Weight:	110 lbs.
Cut out dimensions:	36.22 x 13.18 inch
Voltage / Frequency:	120 V ~ 60 Hz
UL Voltage / Frequency:	115 V ~ 60 Hz
Current 95F95F:	11.2 A
Starting current:	40.1 A
Max. current:	18.8 A
Nominal power 95F95F:	1,28 kW
Max. power:	1,42 kW
Fuse:	20 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block


Performance graph:



Air flow:



Cut out dimensions:



Order Information

Stainless steel housing part no.	4320102
Mit Kondensatverdunstung Bestell Nr.	43201101
Verpackungsmaße	1,015 x 443 x 295 mm
Bruttogewicht	53.5 kg
Taric code	84158200