

Thermoelectric cooler




Description

Order Number:	6205313
Brand Name:	SOLITHERM PELTIER
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress protection to EN 60 529:	IP 66 / UL Type 12, 4, 4X
Note:	The torque for the mounting nuts should be 4.5 Nm.
Approvals:	CE, cURus


Technical data

Cooling capacity 95F/95F:	680 BTU
Air volume flow (system / unimpeded):	Ambient air circuit: 62 / 153 cfm Cabinet air circuit: 90 / 153 cfm
Operating temperature range:	-4°F - 149°F
UL temperature range:	-20°C - 65°C
Mounting:	Recessed
Dimension H x W x D:	19.7 x 13.1 x 7.1 (4.4 + 2.7) inch
Weight:	38 lbs
Cut out dimensions:	472 x 302 mm
Voltage / Frequency:	120 V ~ 60 Hz
Current 95F95F:	2.1 A
Starting current:	3.2 A
Max. current:	2.2 A
Nominal power 95F95F:	250 W
Max. power:	270 W
Fuse:	4 A (T)
Connection:	4 pole power connector 5 pole connector for signals

Performance graph:



Cut out Dimensions:



Order Information

Stainless steel AISI 316 (V4A) housing part no.	62053134
Verpackungsmaße	586.6 x 354 x 227 mm
Bruttogewicht	20.5 kg
Taric code	84158300