

## Thermoelectric cooler



## Description

<b>Order Number:</b>	6805313
<b>Brand Name:</b>	SOLITHERM PELTIER
<b>Housing Material:</b>	Stainless steel AISI 304 (V2A)
<b>Ingress protection to EN 60 529:</b>	IP 66 / UL Type 12, 4, 4X
<b>Note:</b>	The torque for the mounting nuts should be 4.5 Nm.
<b>Approvals:</b>	CE, cURus

## Technical data

<b>Cooling capacity 95F/95F:</b>	2730 BTU
<b>Air volume flow (system / unimpeded):</b>	Ambient air circuit: 280 / 383 cfm Cabinet air circuit: 280 / 383 cfm
<b>Operating temperature range:</b>	-4°F - 149°F
<b>UL temperature range:</b>	-20°C - 65°C
<b>Mounting:</b>	recessed
<b>Dimension H x W x D:</b>	38.4 x 20.3 x 8 (5.3 + 2.7) inch
<b>Weight:</b>	146 lbs.
<b>Cut out dimensions:</b>	18.3 x 36.3 inch
<b>Voltage / Frequency:</b>	120V ~ 60 Hz
<b>Current 95F95F:</b>	8.2 A
<b>Starting current:</b>	14 A
<b>Max. current:</b>	9 A
<b>Nominal power 95F95F:</b>	979 W
<b>Max. power:</b>	1078 W
<b>Fuse:</b>	13 A (T)
<b>Connection:</b>	4 pole power connector 5 pole connector for signals



## Order Information

<b>Stainless steel AISI 316 (V4A) housing part no.</b>	68053134
<b>Verpackungsmaße</b>	1060 x 612 x 260 mm
<b>Bruttogewicht</b>	75.5 kg
<b>Taric code</b>	84158300