

## Roof mounted cooling unit




## Description

<b>Order Number:</b>	951520001
<b>Brand Name:</b>	SLIMLINE PRO TOP
<b>Color:</b>	RAL 7035
<b>Housing Material:</b>	Mild steel, powder coated
<b>Ingress protection to EN 60 529:</b>	NEMA 12
<b>Approvals:</b>	CE, cURus

## Technical data

<b>Cooling capacity 95F/95F:</b>	1550 W
<b>Cooling capacity 95F/122F:</b>	1200 W
<b>Compressor type:</b>	Rotary piston
<b>Refrigerant / GWP:</b>	R513A / 630
<b>Refrigerant charge:</b>	285 g / 10.1 oz.
<b>High / low pressure:</b>	32 / 6 bar 464 / 87 psig
<b>Air volume flow (system / unimpeded):</b>	Umgebungskreislauf: 645 / 850 m <sup>3</sup> /h Schrankkreislauf: 483 / 850 m <sup>3</sup> /h
<b>Operating temperature range:</b>	5°C - 55°C
<b>Mounting:</b>	Roof mounted
<b>Dimension H x W x D:</b>	412 x 595 x 395 mm
<b>Weight:</b>	41.75 kg
<b>Voltage / Frequency:</b>	400/460 V - 50/60 Hz 2~
<b>Current 95F95F:</b>	2.1 A
<b>Starting current:</b>	8 A
<b>Max. current:</b>	3.1 A
<b>Nominal power 95F95F:</b>	770 W
<b>Fuse:</b>	15 A (T)
<b>Short-circuit current rating:</b>	5 kA
<b>Connection:</b>	4 pole connector for power 5 pole connector for signals 3 pole connector for RS 485 MODBUS

**Cut out Dimensions:**



## Order Information

**Mit Edelstahlgehäuse Bestell Nr.**

951520S62

**Zolltarifnummer**

84158200