

Roof mounted air conditioner




Description

Order Number:	950600001
Brand Name:	SLIMLINE PRO TOP
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection to EN 60 529:	NEMA 12
Approvals:	CE, cURus

Technical data

Cooling capacity 95F/95F:	650 W
Cooling capacity 95F/122F:	580W
Compressor type:	Rotary piston
Refrigerant / GWP:	R513A / 630
Refrigerant charge:	123 g / 4.34 oz.
High / low pressure:	28 / 6 bar 406 / 88 psig
Air volume flow (system / unimpeded):	Umgebungskreislauf: 408 m ³ /h Schrankkreislauf: 265 m ³ /h
Operating temperature range:	5°C - 55°C
Mounting:	Roof mounted
Dimension H x W x D:	368 x 400 x 325 mm
Weight:	16.4 kg
Voltage / Frequency:	230 V ~ 50/60 Hz
Current 95F95F:	1.7 A
Starting current:	6 A
Max. current:	2.4 A
Nominal power 95F95F:	350 / 380W
Max. power:	530 W
Fuse:	15 A (T)
Short-circuit current rating:	5 kA
Connection:	4 - poliger Stecker für Stromversorgung 5 - poliger Stecker für Signale 3 - poliger Stecker für RS 485 MODBUS

Cut out Dimensions:



Order Information

Mit Edelstahlgehäuse Bestell Nr.

950600S62

Zolltarifnummer

84158200