

Air to Water Heat Exchanger



Description

Order Number:	2120010
Brand Name:	SLIMLINE HEX
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection to EN 60 529:	IP 55
Approvals:	CE, cURus

Technical data

Cooling capacity 95F/W50F (53 GPH):	5120 BTU
Cooling capacity 95F/W50F (132 GPH):	7165 BTU
Refrigerant / GWP:	Water, light oils or similar
Coolant:	Water, light oils or similar
Air volume flow (system / unimpeded):	636 / 920 m ³ /h
Operating temperature range:	+34°F - +162°F
Mounting:	Wall mounted / internal
Dimension H x W x D:	73.4 x 15.7 x 7.1 inch
Weight:	33 lbs.
Voltage / Frequency:	230 V ~ 50/60 Hz
Starting current:	0.51 / 0.52 A
Max. current:	0.4 / 0.5 A
Max. power:	85 / 100 W
Pressure water circuit:	10 bar
Water connection:	Rp 1/4" - inside thread with 2 connectors for pipe internal diameter of 0.39 in.
Fuse:	2 A (T)
Connection:	3 - pole terminal for alarms 4 - pole terminal for power

Order Information

Stainless steel housing part no.	2120012
Mit Magentventil Bestell Nr.	2120000
Taric code	84158300