

## Enclosure air conditioner type 4X



### Description

<b>Order Number:</b>	57051182
<b>Brand Name:</b>	Compact Outdoor
<b>Housing Material:</b>	Stainless steel AISI 304 (V2A)
<b>Ingress protection to EN 60 529:</b>	IP 56 / Type 12, 3, 3R, 4, 4X
<b>Included:</b>	Mit Schaltschrankheizung und Aluminium Filter
<b>Approvals:</b>	CE, cURus, cULus
<b>UL File Number:</b>	cURus (SA32278), cULus (E498756)

## Technical data

<b>Cooling capacity 95F/95F:</b>	1945 BTU
<b>Cooling capacity 95F/122F:</b>	1520 BTU @ 50 Hz 1670 BTU @ 60 Hz
<b>Enclosure heater:</b>	400 W
<b>Compressor type:</b>	Rotary piston compressor
<b>Refrigerant / GWP:</b>	R513A / 630
<b>Refrigerant charge:</b>	226 g / 7.97 oz.
<b>High / low pressure:</b>	29 / 6 bar 425 / 88 psig
<b>Air volume flow (system / unimpeded):</b>	Ambient air circuit: 185 / 500 cfm Cabinet air circuit: 97 / 147 cfm
<b>Operating temperature range:</b>	-40°F - 131°F
<b>Mounting:</b>	Wall mounted
<b>Dimension H x W x D:</b>	32.68 x 12 x 10.63 inch
<b>Weight:</b>	66 lbs.
<b>Cut out dimensions:</b>	10.43 x 7.09 inch 10.43 x 6.3 inch
<b>Voltage / Frequency:</b>	120 V ~ 50/60 Hz
<b>UL Voltage / Frequency:</b>	115 V ~ 60 Hz
<b>Current 95F95F:</b>	4.2 A @ 50 Hz 3.8 A @ 60 Hz
<b>Starting current:</b>	10.6 A
<b>Max. current:</b>	6.8 A
<b>Nominal power 95F95F:</b>	422 W @ 50 Hz 432 W @ 60 Hz
<b>Max. power:</b>	497 W @ 50 Hz 545 W @ 60 Hz
<b>Fuse:</b>	15 A (T)
<b>Max circuit ampacity:</b>	15 A
<b>Short-circuit current rating:</b>	5 kA
<b>Rated current compressor:</b>	3.2 A

**Full load current fans:**

1.5 A

---

**Connection:**

4-pole terminal block for power  
5-pole terminal block for signals  
3-pole terminal block for RS 485

---



## Order Information

<b>With stainless steel AISI 316 (V4A)</b>	57051184
<b>Verpackungsmaße</b>	870 x 348 x 310 mm
<b>Bruttogewicht</b>	34 kg
<b>Zolltarifnummer</b>	84158200