

## Outdoor air conditioner



## Description

<b>Order Number:</b>	571011201
<b>Brand Name:</b>	Compact Outdoor
<b>Color:</b>	RAL 7035
<b>Housing Material:</b>	Mild steel, powder coated
<b>Ingress protection to EN 60 529:</b>	IP 56 / Type 12, 3, 3R, 4
<b>Included:</b>	Mit Schaltschrankheizung und Aluminium Filter
<b>Approvals:</b>	CE, cURus, cULus
<b>UL File Number:</b>	cURus (SA32278), cULus (E498756)

## Technical data

<b>Cooling capacity 95F/95F:</b>	3410 BTU
<b>Cooling capacity 95F/122F:</b>	1440 BTU
<b>Enclosure heater:</b>	400 W
<b>Compressor type:</b>	Reciprocating compressor
<b>Refrigerant / GWP:</b>	R513A / 630
<b>Refrigerant charge:</b>	291 g / 10.3 oz
<b>High / low pressure:</b>	30.1 / 6 bar 445 / 88 psig
<b>Air volume flow (system / unimpeded):</b>	Ambient air circuit: 190 / 500 cfm Cabinet air circuit: 220 / 324 cfm
<b>Operating temperature range:</b>	-40°F - 131°F
<b>Mounting:</b>	Wall mounted
<b>Dimension H x W x D:</b>	35.43 x 12 x 10.63 inch
<b>Weight:</b>	88 lbs.
<b>Voltage / Frequency:</b>	120 V ~ 50/60 Hz
<b>UL Voltage / Frequency:</b>	115 V ~ 60 Hz
<b>Current 95F95F:</b>	5.2 A @ 50 Hz 5.2 A @ 60 Hz
<b>Starting current:</b>	10.6 A
<b>Max. current:</b>	9.1 A
<b>Nominal power 95F95F:</b>	571 W @ 50 Hz 611 W @ 60 Hz
<b>Max. power:</b>	667 W @ 50 Hz 734 W @ 60 Hz
<b>Fuse:</b>	15 A (T)
<b>Max circuit ampacity:</b>	15 A
<b>Short-circuit current rating:</b>	5 kA
<b>Rated current compressor:</b>	3.2 A
<b>Full load current fans:</b>	1.5 A

**Connection:**

4-pole terminal block for power

5-pole terminal block for signals

3-pole terminal block for RS 485

---



## Order Information

<b>Box dimensions</b>	940 x 348 x 310 mm
<b>Gross weight</b>	42 kg
<b>Taric code</b>	84158200