

Enclosure air conditioner type 4X



Description

| | |
|---|---|
| Order Number: | 57152182 |
| Brand Name: | Compact Outdoor |
| Housing Material: | Stainless steel AISI 304 (V2A) |
| Ingress protection to EN 60 529: | IP 56 / Type 12, 3, 3R, 4, 4X |
| Included: | Mit Schaltschrankheizung und Aluminium Filter |
| Approvals: | CE, cURus, cULus |
| UL File Number: | cURus (SA32278), cULus (E498756) |

Technical data

| | |
|--|--|
| Cooling capacity 95F/95F: | 5120 BTU |
| Cooling capacity 95F/122F: | 4370 BTU |
| Enclosure heater: | 1000 W |
| Compressor type: | Reciprocating compressor |
| Refrigerant / GWP: | R513A / 630 |
| Refrigerant charge: | 558 g / 19.7 oz |
| High / low pressure: | 26 / 6 bar 383 / 88 psig |
| Air volume flow (system / unimpeded): | Ambient air circuit: 385 / 706 cfm Cabinet air circuit: 235 / 324 cfm |
| Operating temperature range: | -40°F - 131°F |
| Mounting: | Wall mounted |
| Dimension H x W x D: | 45.2 x 15.5 x 10.6 inch |
| Weight: | 110 lbs. |
| Voltage / Frequency: | 400/460 V - 50/60 Hz 2~ |
| UL Voltage / Frequency: | 400/460 V ~ 60 Hz 2~ |
| Current 95F95F: | 2.1 A @ 50 Hz 2.5 A @ 60 Hz |
| Starting current: | 8.3 A |
| Max. current: | 3.6 A |
| Nominal power 95F95F: | 801 W @ 50 Hz 961 W @ 60 Hz |
| Max. power: | 992 W @ 50 Hz 1175 W @ 60 Hz |
| Fuse: | 15 A (T) |
| Max circuit ampacity: | 15 A |
| Short-circuit current rating: | 5 kA |
| Rated current compressor: | 1.4 A |
| Full load current fans: | 0.4 A |

Connection:

4-pole terminal block for power

5-pole terminal block for signals

3-pole terminal block for RS 485

Order Information

| | |
|--|----------------------|
| With stainless steel AISI 316 (V4A) | 57152184 |
| Verpackungsmaße | 1,190 x 443 x 310 mm |
| Bruttogewicht | 53 kg |
| Zolltarifnummer | 84158200 |