

## Outdoor air conditioner



### Description

<b>Order Number:</b>	574101201
<b>Brand Name:</b>	Compact Outdoor
<b>Color:</b>	RAL 7035
<b>Housing Material:</b>	Mild steel, powder coated
<b>Ingress protection to EN 60 529:</b>	IP 56 / Type 12, 3, 3R, 4
<b>Included:</b>	Mit Schaltschrankheizung und Aluminium Filter
<b>Approvals:</b>	CE, cURus, cULus
<b>UL File Number:</b>	cURus (SA32278), cULus (E498756)


## Technical data

<b>Cooling capacity 95F/95F:</b>	13650 BTU @ 50 Hz 13650 @ 60 Hz
<b>Cooling capacity 95F/122F:</b>	10850 BTU @ 50 Hz 11465 BTU @ 60 Hz
<b>Enclosure heater:</b>	2000 W
<b>Compressor type:</b>	Rotary piston compressor
<b>Refrigerant / GWP:</b>	R513A / 630
<b>Refrigerant charge:</b>	1217 g / 42.9 oz.
<b>High / low pressure:</b>	3.0 / 0.5 MPa 433 / 77 psig
<b>Air volume flow (system / unimpeded):</b>	Ambient air circuit: 583 / 883 cfm Cabinet air circuit: 560 / 706 cfm
<b>Operating temperature range:</b>	-40°F - 131°F
<b>Mounting:</b>	Wall mounted
<b>Dimension H x W x D:</b>	61 x 18 x 14 inch
<b>Weight:</b>	181 lbs.
<b>Voltage / Frequency:</b>	230 V ~ 50/60 Hz
<b>UL Voltage / Frequency:</b>	230 V ~ 60 Hz
<b>Current 95F95F:</b>	9.5 A @ 50 Hz 12.5 A @ 60 Hz
<b>Starting current:</b>	42 A
<b>Max. current:</b>	15.2 A
<b>Nominal power 95F95F:</b>	2160 W @ 50 Hz 2790 W @ 60 Hz
<b>Max. power:</b>	2620 W @ 50 Hz 3480 kW @ 60 Hz
<b>Fuse:</b>	20 A (T)
<b>Max circuit ampacity:</b>	15 A
<b>Short-circuit current rating:</b>	5 kA
<b>Rated current compressor:</b>	7.6 A
<b>Full load current fans:</b>	1.5 A

**Connection:**

4 pole terminal block for power  
5 pole terminal block for signals  
3 pole terminal block for RS 485

---





## Order Information

<b>Box dimensions</b>	1,590 x 503 x 395 mm
<b>Gross weight</b>	86 kg
<b>Taric code</b>	84158200