

## Air to air heat exchanger



## Description

|   |                           |
|---|---------------------------|
| <b>Order Number:</b>                    | 580071001                 |
| <b>Brand Name:</b>                      | SLIMLINE HEX              |
| <b>Color:</b>                           | RAL 7035                  |
| <b>Housing Material:</b>                | Mild steel, powder coated |
| <b>Ingress protection to EN 60 529:</b> | IP 54 / NEMA 12           |
| <b>Approvals:</b>                       | CE, cURus                 |
| <b>UL File Number:</b>                  | SA9672                    |

## Technical data

|  |  |
|--|--|
| <b>Heat exchanger performance:</b>           | 4 W/F  |
| <b>Air volume flow (system / unimpeded):</b> | Ambient air circuit: 45 / 177 cfm<br>Cabinet air circuit: 51 / 177 cfm |
| <b>Operating temperature range:</b>          | 23°F - 131°F   |
| <b>Mounting:</b>                             | Wall mounted   |
| <b>Dimension H x W x D:</b>                  | 20 x 7.7 x 6 inch  |
| <b>Weight:</b>                               | 16.5 lbs   |
| <b>Voltage / Frequency:</b>                  | 120 V ~ 60 Hz  |
| <b>UL Voltage / Frequency:</b>               | 120 V ~ 60 Hz  |
| <b>Starting current:</b>                     | 1.3 A  |
| <b>Max. current:</b>                         | 1.1 A  |
| <b>Max. power:</b>                           | 65 W   |
| <b>Fuse:</b>                                 | 1.6 A (T)  |
| <b>Connection:</b>                           | 8 - pin Connector  |



## Order Information

|   |                    |
|---|--------------------|
| <b>Stainless steel housing part no.</b> | 58007102           |
| <b>Verpackungsmaße</b>                  | 560 x 274 x 206 mm |
| <b>Bruttogewicht</b>                    | 9.5 kg             |
| <b>Taric code</b>                       | 84158300           |
| <b>GTIN (EAN)</b>                       | 5350604200012      |