

## Air to Water Heat Exchanger




### Description

<b>Order Number:</b>	2300110
<b>Brand Name:</b>	SLIMLINE HEX
<b>Color:</b>	RAL 7035
<b>Housing Material:</b>	Mild steel, powder coated
<b>Ingress protection:</b>	IP 55
<b>Approvals:</b>	CE, cURus


## Technical data

<b>Cooling capacity 95F/W50F (53 GPH):</b>	1090 BTU
<b>Coolant:</b>	Water, light oils or similar
<b>Operating temperature range:</b>	34°F ... +149°F
<b>Air volume flow (system / unimpeded):</b>	50 / 141 cfm
<b>Mounting:</b>	Wall mounted / Internal
<b>Dimension H x W x D:</b>	11.93 x 6.02 x 3.31 in.
<b>Weight:</b>	9.92 lbs.
<b>Voltage / Frequency:</b>	120 V ~ 60 Hz
<b>Starting current:</b>	0.74 A
<b>Max. current:</b>	0.49 A
<b>Max. power:</b>	38 W
<b>Pressure water circuit:</b>	10 bar
<b>Water connection:</b>	Rp 1/4" - inside thread with 2 connectors for pipe internal diameter of 0.39 inch
<b>Fuse:</b>	4 A (T)
<b>Connection:</b>	Connection Terminals


**Performance graph:**



**Air flow:**



**Cut out dimensions:**



## Order Information

<b>Stainless steel housing part no.</b>	2300112
<b>Verpackungsmaße</b>	408.6 x 169 x 120.5 mm
<b>Bruttogewicht</b>	5.3 kg
<b>Taric code</b>	84158300