

Enclosure air conditioner



Description

Order Number:	850300001
Brand Name:	SLIMLINE PRO
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection to EN 60 529:	Type 3, 3R, 12, 4
Approvals:	CE, cURus, cULus

Technical data

Cooling capacity 95F/95F:	1200 BTU @ 50 Hz 1200 BTU @ 60 Hz
Cooling capacity 95F/122F:	685 BTU @ 50 Hz 715 BTU @ 60 Hz
EER 95F95F:	1.13
Compressor type:	Rotary piston
Refrigerant / GWP:	R 513A / 630
Refrigerant charge:	86 g / 3 oz
High / low pressure:	28 / 6 bar 406 / 88 psi
Air volume flow (system / unimpeded):	Ambient air circuit: 118 / 240 cfm Cabinet air circuit: 72 / 106 cfm
Operating temperature range:	50°F - 140°F
UL temperature range:	50°F - 140°F
Mounting:	Wall mounted / recessed
Dimension H x W x D:	23.7 x 9.9 x 5.4 inch
Weight:	30.8 lbs.
Voltage / Frequency:	230 V ~ 50/60 Hz
UL Voltage / Frequency:	230 V ~ 60 Hz
Current 95F95F:	1.5 A @ 50 Hz 1.4 A @ 60 Hz
Starting current:	3.4 A
Max. current:	1.7 A
Nominal power 95F95F:	310 W @ 50 Hz 300 W @ 60 Hz
Max. power:	370 W
Fuse:	15 A (T)
Max circuit ampacity:	15 A
Short-circuit current rating:	5 kA
Rated current compressor:	1 A
Full load current fans:	0.2 A


Connection:

4 pole terminal block for power


5 pole terminal block for signals

3 pole terminal block for RS 485

Performance graph:



Cut out Dimensions:



Order Information

Box dimensions	692 x 285 x 192 mm
Gross weight	14.5 kg
Taric Code	84158200