

Enclosure air conditioner - Outdoor



Description

Order Number:	850820001
Brand Name:	SLIMLINE PRO
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection:	Type 3, 3R, 12, 4
Approvals:	CE, cURus, cULus

Technical data

Cooling capacity 95F/95F:	2815 BTU @ 50 Hz 2970 BTU @ 60 Hz
Cooling capacity 95F/122F:	2800 BTU @ 50 Hz 2850 BTU @ 60 Hz
EER 95F95F:	1.80
Compressor type:	Rotary piston
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	175 g / 6.2 oz
High / low pressure:	30 / 6 bar 435 / 88 psi
Operating temperature range:	50°F - 140°F
UL temperature range:	50°F - 131°F
Air volume flow (system / unimpeded):	Ambient air circuit: 220 / 380 cfm Cabinet air circuit: 205 / 323 cfm
Mounting:	Wall mounted / recessed
Dimension H x W x D:	37.5 x 12.1 x 8.3 inch
Weight:	66 lbs.
Voltage / Frequency:	400/460 V - 50/60 Hz 2~
UL Voltage / Frequency:	460 V / 60Hz 2~
Current 95F95F:	1.2 A @ 50 Hz 1.15 A @ 60 Hz
Starting current:	4.0 A
Max. current:	1.7 A
Nominal power 95F95F:	460 W @ 50 Hz 520 W @ 60 Hz
Max. power:	690 W
Fuse:	15 A (T)
Max circuit ampacity:	15 A
Short-circuit current rating:	5 kA
Rated current compressor:	0.9 A


Full load current fans:

0.7 A


Connection:

4 pole terminal block for power
5 pole terminal block for signals
3 pole terminal block for RS 485

Performance graph:



Cut out dimensions:



Order Information

Box dimensions 1042 x 405 x 242 mm

Gross weight 31 Kg

Taric code 84158200