

Enclosure air conditioner



Description


Order Number:	854020001
Brand Name:	SLIMLINE PRO
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection:	Type 3, 3R, 12, 4
Approvals:	CE, cURus, cULus

Technical data


Cooling capacity 95F/95F:	13650 BTU @ 50 Hz 14300 BTU @ 60 Hz
Cooling capacity 95F/122F:	11950 BTU @ 50 Hz 13300 BTU @ 60 Hz
EER 95F95F:	2.31
Compressor type:	Rotary piston
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	570 g / 20.1 oz.
High / low pressure:	32 / 6 bar 460 / 88 psi
Operating temperature range:	50°F - 140°F
UL temperature range:	50°F - 140°F
Air volume flow (system / unimpeded):	Ambient: 590 / 825 cfm Enclosure: 441 / 706 cfm
Mounting:	Wall mounted / recessed
Dimension H x W x D:	1550 x 455 x 270 mm
Weight:	136 lbs.
Voltage / Frequency:	380-415 V 50 Hz 3~ 400-460 V 60 Hz 3~
UL Voltage / Frequency:	460 V / 60Hz 3~
Current 95F95F:	3.5 A @ 50 Hz 3.7 A @ 60 Hz
Starting current:	15 A
Max. current:	4.8 A
Nominal power 95F95F:	1.73 kW @ 50 Hz 2.27 kW @ 60 Hz
Max. power:	3.2 kW
Fuse:	15 A (T)
Max circuit ampacity:	15 A
Short-circuit current rating:	5 kA

Rated current compressor:	3 A
Full load current fans:	1.3 A
Connection:	4 pole terminal block for power 5 pole terminal block for signals 3 pole terminal block for RS 485

Performance graph:



Cut out dimensions:



Order Information

Box dimensions 1642 x 555 x 299 mm

Gross weight 70 Kg

Taric code 84158200