

## Enclosure air conditioner



## Description

<b>Order Number:</b>	850600S62
<b>Brand Name:</b>	SLIMLINE PRO
<b>Housing Material:</b>	Stainless steel AISI 304 (V2A)
<b>Ingress protection:</b>	IP 56 / Type 12, 3, 3R, 4, 4X
<b>Approvals:</b>	CE, cURus, cULus

## Technical data

<b>Cooling capacity 95F/95F:</b>	2285 BTU @ 50 Hz 2320 BTU @ 60 Hz
<b>Cooling capacity 95F/122F:</b>	1740 BTU/hr @ 50 Hz 1825 BTU/hr @ 60 Hz
<b>EER 95F95F:</b>	1.55
<b>Compressor type:</b>	Rotary piston
<b>Refrigerant / GWP:</b>	R134a / 1430
<b>Refrigerant charge:</b>	117 g / 3.46 oz.
<b>High / low pressure:</b>	28 / 6 bar 406 / 88 psi
<b>Operating temperature range:</b>	50°F - 140°F
<b>UL temperature range:</b>	50°F - 131°F
<b>Air volume flow (system / unimpeded):</b>	Ambient air circuit: 117 / 240 cfm Enclosure circuit: 72 / 106 cfm
<b>Mounting:</b>	Wall mounted / recessed
<b>Dimension H x W x D:</b>	23.7 x 9.9 x 5.4 inch
<b>Weight:</b>	30.86 lbs.
<b>Voltage / Frequency:</b>	230 V ~ 50/60 Hz
<b>UL Voltage / Frequency:</b>	230 V ~ 60 Hz
<b>Current 95F95F:</b>	1.9 A @ 50Hz 1.8 A @ 60Hz
<b>Starting current:</b>	6 A
<b>Max. current:</b>	2.7 A
<b>Nominal power 95F95F:</b>	410 W @ 50 Hz 430 W @ 60 Hz
<b>Max. power:</b>	620 W
<b>Fuse:</b>	15 A (T)
<b>Max circuit ampacity:</b>	15 A
<b>Short-circuit current rating:</b>	5 kA
<b>Rated current compressor:</b>	1.6 A

**Full load current fans:**

0.2 A


---

**Connection:**

4 pole terminal block for power  
5 pole terminal block for signals  
3 pole terminal block for RS 485

---

**Cut out dimensions:**



## Order Information

<b>Verpackungsmaße</b>	692 x 285 x 192 mm
<b>Bruttogewicht</b>	16 Kg
<b>Zolltarifnummer</b>	84158200