

Filter fan SF 4725 - 100-240V




Description

Order Number:	4725852201
Brand Name:	SOLIVENT PRO
Color:	RAL 7035
Housing Material:	PC plastic
Ingress protection to EN 60 529:	IP 54
UL Typ (UL 50E):	12
Note:	IP 55 with filter O3 (see manual)
Approvals:	CE, cURus, cULus
UL File Number:	E498756


Technical data

Air flow unimpeded IP 54:	112 CFM
Air flow with exhaust filter IP 54:	94 CFM
Air flow unimpeded Type 12:	139 / 156 CFM
Operating temperature range:	14°F - 131°F
Storage temperature range:	-40°F - 158°F
Mounting:	Wall mounted
Dimension H x W x D:	10.06 × 10.06 × 4.43 inches
Weight:	2.65 lbs.
Cut out dimensions:	8.82 x 8.82 inch
Voltage / Frequency:	120-240 V ~ 50/60 Hz
Rated current:	0.18 / 0.18 A
Power consumption:	15 / 15 W
Degree of separation IP 54:	67 % - DIN 24185
Degree of separation IP 55:	85 % - DIN 24185
Wall thickness:	0.039 - 0.118 inch
Noise level:	51.5 dB (A)
Fuse:	1 A(T)
Connection:	Spring terminal


Air flow:



Cooling capacity:



Cut out Dimensions:



Order Information

Order number	IP rating	UL Type	RAL colour	Flow type ¹⁾	Air flow (m ³ /h) ²⁾	Air flow with exhaust filter (m ³ /h)
4725852201	54	12 / 3R	RAL 7035	B	190 m ³ /hr	160 m ³ /hr
4725852203	54	12 / 3R	RAL 9005	B	190 m ³ /hr	160 m ³ /hr
4725853201	55	12 / 3R	RAL 7035	B	178 m ³ /hr	141 m ³ /hr
4725853203	55	12 / 3R	RAL 9005	B	178 m ³ /hr	141 m ³ /hr
472585R2201	54	12 / 3R	RAL 7035	S	176 m ³ /hr	N/A
472585R2203	54	12 / 3R	RAL 9005	S	176 m ³ /hr	N/A
472585R3201	55	12 / 3R	RAL 7035	S	166 m ³ /hr	N/A
472585R3203	55	12 / 3R	RAL 9005	S	166 m ³ /hr	N/A

¹⁾ B = Blowing - from ambient into the enclosure (standard version)
 S = Suction - from enclosure to ambient (on request)

²⁾ unimpeded 50/60 Hz

Zolltarifnummer

84145915