SEIFERT

Filter fan SF 4725 - 24V


Description

Order Number:	4725352201
Brand Name:	SOLIVENT PRO
Color:	RAL 7035
Housing Material:	PC plastic
Ingress protection to EN 60 529:	IP 54
UL Typ (UL 50E):	12
Note:	IP 55 with filter O3 (see manual)
Approvals:	CE, cURus, cULus
UL File Number:	E498756

Technical data

|	
Air flow unimpeded IP 54:	108 CFM
Air flow with exhaust filter IP 54:	87 CFM
Air flow unimpeded Type 12:	139 / 156 CFM
Operating temperature range:	14°F - 131°F
Storage temperature range:	-40°F - 158°F
Mounting:	Wall mounted
Dimension H x W x D:	255.4 x 255.5 x 112.5 (11.6+100.9) mm
Weight:	2.65 lbs.
Cut out dimensions:	8.82 x 8.82 inch
Voltage / Frequency:	24 V
Rated current:	0.5 A
Power consumption:	12 W
Degree of seperation IP 54:	67 % - DIN 24185
Degree of seperation IP 55:	85 % - DIN 24185
Wall thickness:	0.039 - 0.118 inch
Noise level:	50 dB (A)
Fuse:	1 A (T)
Connection:	Spring terminal

Air flow:

Cooling capacity:

Cut out Dimensions:

Order Information

Order number	IP rating	UL Type	RAL colour	Flow type[1]	Air flow (m³/h)[2]	Air flow with exhaust filter (m³/h)
4725352201	54	12 / 3R	RAL 7035	B	183 m³/hr	147 m³/hr
4725352203	54	12 / 3R	RAL 9005	B	183 m³/hr	147 m³/hr
4725353201	55	12 / 3R	RAL 7035	B	180 m³/hr	129 m³/hr
4725353203	55	12 / 3R	RAL 9005	B	180 m³/hr	129 m³/hr
472535R2201	54	12 / 3R	RAL 7035	S	175 m³/hr	N/A
472535R2203	54	12 / 3R	RAL 9005	S	175 m³/hr	N/A
472535R3201	55	12 / 3R	RAL 7035	S	164 m³/hr	N/A
472535R3203	55	12 / 3R	RAL 9005	S	164 m³/hr	N/A

[1] B = Blowing – from ambient into the enclosure (standard version)
S = Suction – from enclosure to ambient (on request)

[2] unimpeded 50/60 Hz

Zolltarifnummer	84145915