

## Enclosure air conditioner



## Description

<b>Order Number:</b>	841200001
<b>Brand Name:</b>	SLIMLINE PRO
<b>Color:</b>	RAL 7035
<b>Housing Material:</b>	Mild steel, powder coated
<b>Ingress protection:</b>	IP 55 / Type 12
<b>Note:</b>	Has the same cutout like KG 8508 and KG 8512
<b>Approvals:</b>	CE, cURus, cULus

## Technical data

<b>Cooling capacity 95F/95F:</b>	5120 BTU @ 50 Hz 5290 BTU @ 60 Hz
<b>Cooling capacity 95F/122F:</b>	4330 BTU @ 50 Hz 4540 BTU @ 60 Hz
<b>EER 95F95F:</b>	2.20
<b>Compressor type:</b>	Rotary piston
<b>Refrigerant / GWP:</b>	R134a / 1430
<b>Refrigerant charge:</b>	267 g / 9.4 oz
<b>High / low pressure:</b>	30 / 6 bar 435 / 88 psi
<b>Operating temperature range:</b>	50°F - 140°F
<b>UL temperature range:</b>	50°F - 140°F
<b>Air volume flow (system / unimpeded):</b>	Ambient: 323 / 500 m <sup>3</sup> /h Enclosure: 206 / 500 m <sup>3</sup> /h
<b>Mounting:</b>	Wall mounted / recessed
<b>Dimension H x W x D:</b>	37.5 x 15.6 x 9.9 inch
<b>Weight:</b>	38.5 kg
<b>Voltage / Frequency:</b>	230 V ~ 50/60 Hz
<b>UL Voltage / Frequency:</b>	230 V ~ 60 Hz
<b>Current 95F95F:</b>	3.2 A @ 50 Hz 3.6 A @ 60 Hz
<b>Starting current:</b>	16 A
<b>Max. current:</b>	4.7 A
<b>Nominal power 95F95F:</b>	680 W @ 50 Hz 830 W @ 60 Hz
<b>Max. power:</b>	1.1 kW
<b>Fuse:</b>	15 A (T)
<b>Max circuit ampacity:</b>	15 A
<b>Short-circuit current rating:</b>	5 kA
<b>Rated current compressor:</b>	2.5 A


**Full load current fans:** 0.7 A

---

**Connection:** 4 - poliger Stecker für Versorgungsspannung  
5 - poliger Stecker für Signale  
3 - poliger Stecker für RS 485

---

**Cut out dimensions:**



## Order Information

<b>Box dimensions</b>	1042 x 495 x 283 mm
<b>Gross weight</b>	44 Kg
<b>Taric code</b>	84158200