

Enclosure air conditioner



Description

| | |
|---|---|
| Order Number: | 841220S62 |
| Brand Name: | SLIMLINE PRO |
| Housing Material: | Stainless steel AISI 304 (V2A) |
| Ingress protection to EN 60 529: | IP 56 / Type 12, 3, 3R, 4, 4X |
| Note: | Hat denselben Schaltschrankausbruch wie KG 8508 und KG 8512 |
| Approvals: | CE, cURus, cULus |


Technical data

| | |
|--|--|
| Cooling capacity 95F/95F: | 5120 BTU @ 50 Hz 5630 BTU @ 60 Hz |
| Cooling capacity 95F/122F: | 4440 BTU @ 50 Hz 4950 BTU @ 60 Hz |
| EER 95F95F: | 2.1 / 1.8 |
| Compressor type: | Rotary piston |
| Refrigerant / GWP: | R 513A / 630 |
| Refrigerant charge: | 247 g / 8.7 oz. |
| High / low pressure: | 30 / 6 bar 435 / 88 psi |
| Air volume flow (system / unimpeded): | Ambient: 323 / 500 m ³ /h Enclosure: 206 / 500 m ³ /h |
| Operating temperature range: | 50°F - 140°F |
| UL temperature range: | 50°F - 140°F |
| Mounting: | Wall mounted / recessed |
| Dimension H x W x D: | 37.5 x 15.6 x 9.9 inch |
| Weight: | 88 lbs |
| Voltage / Frequency: | 380-415 V 50 Hz 3~ 400-460 V 60 Hz 3~ |
| UL Voltage / Frequency: | 460 V / 60Hz 3~ |
| Current 95F95F: | 1.6 A @ 50 Hz 1.6 A @ 60 Hz |
| Starting current: | 8.2 A |
| Max. current: | 1.9 A |
| Nominal power 95F95F: | 710 W @ 50 Hz 910 W @ 60 Hz |
| Max. power: | 940 W @ 50 Hz 1150 W @ 60 Hz |
| Fuse: | 15 A (T) |
| Max circuit ampacity: | 15 A |
| Short-circuit current rating: | 5 kA |
| Rated current compressor: | 1.3 A |

Full load current fans: 1.3 A

Connection: 4 - poliger Stecker für Versorgungsspannung
5 - poliger Stecker für Signale
3 - poliger Stecker für RS 485

Cut out Dimensions:



Order Information

Box dimensions 1042 x 495 x 283 mm

Gross weight 46 Kg

Taric code 84158200